
Tubing clamp systems

RQDR-PS

Tubing clamp systems for light, medium and heavy duty applications

Rotatable tubing holder for mounting on profile rails / maximum mobility with red MOVE insert, especially for cobots and small industrial robots at slow and medium speeds in the field of robotics.





Temperature:	-40°C ... +120°C
Material:	PA plastics (PA6)

APPLICATIONS:

- Robotics
- especially for Cobots and small industrial robots at slow and medium speeds.

FLEXA No.	Colour	OD [mm]	A [mm]	B [mm]	C [mm]	Weight [kg/100]	PU [pcs.]
15040042202	Black	42.5	66.0	86.0	30.0	4.50	1
15040142202	Black	with MOVE OD 34.5	66.0	86.0	30.0	5.60	1
15040242202	Black	with MOVE OD 28.5	66.0	86.0	30.0	5.84	1
15040342202	Black	with MOVE OD 21.2	66.0	86.0	30.0	6.20	1
15040442202	Black	with RQMR OD 34.5	66.0	86.0	30.0	5.60	1
15040542202	Black	with RQMR OD 28.5	66.0	86.0	30.0	6.20	1
15040642202	Black	with RQMR OD 21.2	66.0	86.0	30.0	6.30	1

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA´s knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.