

Model	Code	Cable nr. - Ø cables [mm]	Dimensions [mm]			Pcs /pack
			Thread	Ø Cut-out	Ø Plate	
DES-PDMU 20G	1732030120	1 - max. 10,5	M20	20,5	36	10
DES-PDMU 25G	1732030125	1 - max. 16	M25	25,5	40	
DES-PDMU 32G	1732030132	1 - max. 22	M32	32,5	46	
DES-PDMU 20B	1732031120	1 - max. 10,5	M20	20,5	36	
DES-PDMU 25B	1732031125	1 - max. 16	M25	25,5	40	
DES-PDMU 32B	1732031132	1 - max. 22	M32	32,5	46	

Round cable entry plates with internal frame and double membrane for single cable

- ▶ Metric sized
- ▶ High retaining force thanks to the double membrane
- ▶ Cost efficient solution
- ▶ High IP grade (IP66)



Double membrane



The cable entry plates series DES-PDMU are used to save space and time as alternative to cable glands. They use the metric holes on cabinets or machinery and the nutlock guarantees a strong strain relief and highest water and dust protection.

The cable is pushed through the front membrane, whilst the second membrane increases the strain relief and liquid resistance.

Technical data

Material: TPE

Flammability: self-extinguishing acc. to UL94-V0

Temperature: -40°C... +105°C (static)

Features: halogens and silicones free

Related products

Hydraulic punch driver HY360

Dimensions [mm]

